

# Reformat Code Dialog

## Code | Reformat Code

Ctrl+Alt+L

In this dialog box, specify the scope to apply reformatting to.

Item	Description
File <fully qualified file name>	Choose this option to have all the source code in the current file reformatted.
Selected text	Choose this option to have the currently selected fragment of source code reformatted.
All files in directory <fully qualified directory name>	Select this option to have the source code in all the files in the current directory reformatted at once.
Include subdirectories	Select this check box to have source code from files in the nested directories reformatted. This check box only appears when the nested directories exist.
Optimize imports	Select this check box to remove unused import statements from the code within the selected scope.
Rearrange entries	Select this check box to reorder your source code entries.
Only VCS changed text	If this check box is selected, then reformatting will apply only to the files that have been <a href="#">changed locally</a> , but not yet checked in to the repository. This check box is only available for the files under version control.
Do not show this dialog in the future	Select this check box to perform reformatting silently. To reset this setting, select the check box <b>Show 'Reformat Code' dialog</b> on the <a href="#">Editor page</a> of the <b>Settings</b> dialog ( <b>File   Settings   Editor</b> ).
Run	Click this button to start reformatting the source code within the specified scope.

## See Also

Procedures:

- [Reformatting Source Code](#)

Reference:

- [Code Style](#)

Web Resources:

- [Developer Community](#) 