


# Web Module Editor - Servlet Initialization Parameters

---




## General

---

The pane appears in two cases:

- When you click **OK** in the [New Servlet](#) dialog box.
- When you select a servlet in the **Servlets Configured** pane of the [General](#) tab, and click the  toolbar button or select **Edit** on the context menu.

Use this pane to specify the initialization attributes that allow a servlet to read persistent configuration data, to initialize resources, and to perform any other one-time activities by overriding the `init` method of the Servlet interface.

Item	Description
	Click this button to add a new initialization parameter to the servlet in the <code>web.xml</code> descriptor.
	Click this button to remove the selected initialization parameter of the servlet from the <code>web.xml</code> descriptor.
	Click this button to view the context help page.
Param Name	In this field, specify the name of the new/selected parameter. In the <code>web.xml</code> , it will be presented enclosed in the <code>&lt;param-name&gt;</code> tag.
Param Value	In this field, specify the value of the parameter. In the <code>web.xml</code> , it will be presented enclosed in the <code>&lt;param-value&gt;</code> tag.
Description	In this field, provide a description of the parameter. In the <code>web.xml</code> , it will be presented enclosed in the <code>&lt;description&gt;</code> tag.

## See Also

Concepts:

- [Struts 2](#)

Procedures:

- [Java EE](#)
- [Defining the Servlet Element](#)
- [Specifying the Servlet Initialization Parameters](#)

Reference:

- [Web Module Editor](#)
- [Web Module Editor - General](#)

Web Resources:

- [Developer Community](#) 